

## 8164 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

For more Information  
please call

1-800-Belden1



### General Description:

24 AWG stranded (7x32) TC conductors, Datalene® insulation, twisted pairs individually Beldfoil® shielded + overall 100% Beldfoil + TC braid shield (65% coverage), drain wire, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	24	7x32	TC - Tinned Copper

Total Number of Conductors: 8

#### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Datalene®	FPE - Foam Polyethylene	0.483

#### Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil® (Z-Fold®)	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG
24

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	65

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	1.219

#### Overall Cable

Overall Nominal Diameter: 9.855 mm

#### Pair

Pair Color Code Chart:

Number	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue

### Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +60°C

UL Temperature Rating: 60°C

Bulk Cable Weight: 107.150 Kg/Km

Max. Recommended Pulling Tension: 493.750 N

Min. Bend Radius/Minor Axis: 101.600 mm

## 8164 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 2493 (300 V 60°C)
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

Impedance (Ohm)  
100

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)  
41.0125

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)  
72.182

#### Nominal Velocity of Propagation:

VP (%)  
78

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)  
78.744

#### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)  
10.4992

Ind. Pair Nominal Shield DC Resistance @ 20 Deg. C: 59.058 Ohm/km

#### Max. Operating Voltage - UL:

Voltage  
300 V RMS

#### Max. Recommended Current:

Current  
2.5 Amps per conductor @ 25°C

### Notes (Overall)

**Notes:** Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8164 060100	100 FT	8.200 LB	CHROME		4 FS PR #24 FHDPE SH PVC
8164 0601000	1,000 FT	77.000 LB	CHROME	C	4 FS PR #24 FHDPE SH PVC
8164 060500	500 FT	39.500 LB	CHROME	C	4 FS PR #24 FHDPE SH PVC

**Notes:**

C = CRATE REEL PUT-UP.

### 8164 Multi-Conductor - Low Capacitance Computer Cable for EIA RS-232/422 & Digital

Revision Number: 2    Revision Date: 08-16-2012

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.  
Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.  
All sales of Belden products are subject to Belden's standard terms and conditions of sale.  
Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.  
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.