

EAO – Your Expert Partner for Human Machine Interfaces

951F2000-W0 - Stop switch

951F2000-W0 - Stop switch



Attention: The preview is based on a sample product. This can differ from your current configuration.

Mounting

Behind panel depth	55 mm
Mounting cut-out	Ø 16 mm
Design	raised

Front

Front shape	round
Front dimension	Ø 24 mm

Other Attributes

Weight	0,018 kg
--------	----------

Operating-/Indication part

Lens optics	opaque
Lens material	Plastic
Lens colour	red
Lens profile	Mushroom
Lens illumination	non-illuminative

IP-Rating

Front protection	IP65
------------------	------

Connection Method

Terminal	Solder 2.8 x 0.5 mm
----------	---------------------

Actuator

Switching action	Maintained
------------------	------------

Switching element

Switching current	5 A
Contacts	1 NC
Switching system	Slow-make switching element
Contact material	Silver
Switching voltage	250 V AC


Function

Stop switch


EAO – Your Expert Partner for Human Machine Interfaces

951F2000-W0 - Stop switch


Dimensions



Mounting cut-outs



Wiring diagram



Additional information

Twist to unlock clockwise

Use the location strip no. 260-0020-00 for anti-twisting of the front bezel. At momentary position the overturning force is max. 60 Ncm.