



Specifications		
Nominal Voltage [V]		3.6
Typical capacity [mAh]		320
Size [mm]		According to the drawing
Typical charge [mA]		32(15 hrs)
Accelerated charge [mA]		64 (temp.20 °C)
Maksimum discharge current [mA]		160(temp. 20 °C)
Charge temperature	Typical	0 °C do 45 °C
Discharge temperature	Continuous	-20 °C do 45 °C
Storage temperature	Recommended	-20 °C do 30 °C

Material/ Materiał:	Scale/ Skala: 1:1	Format/ Format arkusza: A4	Weight/ Masa:	Sheet/ Arkusz: /	Version/ Wersja: _
Finishing/ Wykończenie : _	Date/ Data:				Revision/ Rewizja: _
Designed by/ Konstruował:					
Checked by/ Sprawdził:					ERP system number:
Approved by/ Zatwierdził:					77696
Update/ Aktualizował:	Update/ Data aktualizacji:	Date of implementation/ Data wykonania:	Product reference/ Nazwa:	Docum. number/ Nr rysunku:	
J. Dadacz		2016-11-10	ACCU-280PIRAMID CPG H320BC 3,60V 0,32Ah guzi		

S/DZIAŁ\_BADAN\_I\_ROZWOJU/PUBLIKNYPROJEKTY\_NIEADZKOROWANE\_PRZEZ\_DT/IME\_77696\_CPG\_H320BC\_3,60V\_0,32Ah\_guzi