



- DRAWING
- | | | |
|-------|---|---|
| J1 | 1 | 1 |
| | 2 | 2 |
| | 3 | 3 |
| SHELL | 4 | 4 |
| | 5 | 5 |
| J2 | 1 | 1 |
| | 2 | 2 |
| | 3 | 3 |
| SHELL | 4 | 4 |
| | 5 | 5 |

1.CABLE:UL 2725,USB CABLE,28AWG(7/0.12mm)x1PAIRS
 +24AWG(7/0.2mm)x2C,TIN COPPER
 SHIELD:AL-FDIL+7/0.1mmDRAIN WIRE+2x16/0.1mm
 BRAID TIN COPPER
 JACKET:PVC,D.D:4.8mm±0.2mm,COLOR:GREY COLDR
 2.CONNECTOR:2 PCS USB A SOLDER FEMALE GOLD FLASH
 3.HOOD:MODULING TYPE,COLOR:GREY
 4.2 PCS 5 PIN IDE FEMALE,COLOR:BLACK
 5.USB A FEMALE BRACKET
 6.4 SETS NUTS
 7.2 PCS TUBE
 8.FULFILL ROHS Guideline
 9.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

PART NO	AK674	SHEET NO	1	THIRD ANGLE PROJECTION	
TITLE:2 *USB A FEMALE TO 2* 5P IDE FEMALE				SCALE	N.T.S
L:0.25M,UL2725,GREY COLDR				SIZE	A4
DWN NO	D-AK674	UNIT	<input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	CHECKED BY & DATE	APPROVED BY & DATE

