# BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

#### ATS-52210G-C1-R0

21.00 x 21.00 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type:maxiFLOWHeat Sink Attachment:Thermal TapeEquivalent Part Number:ATS-52210G-C2-R0

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- maxiFLOW<sup>™</sup> design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	7.2 °C/W	5.9 °C/W	5.1 °C/W	4.6 °C/W	4.2 °C/W	3.9 °C/W	3.7 °C/W
	Ducted Flow	5.7	N/A	N/A	N/A	N/A	N/A	N/A

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	21.00 mm	21.00 mm	12.50 mm	38.16 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimension</li> <li>ATS-5221 (Saint-Gol</li> <li>Thermal p application</li> <li>ATS resen performant</li> <li>ATS certification</li> </ul>	0G-C2-R0 is the exa bain C675). performance data are n. rves the right to upda nce. ies that this heat sin	emponent size. neight from the bottor act heat sink assemb e provided for referer ate or change its proo k assembly is RoHS astom options availab	oly with an equivalen nce only. Actual perfe ducts without notice -6 and REACH comp	t thermal	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.

