


**NIEIZOLOWANE • RURKOWE**  
NOT INSULATED FROM TUBE




MATERIAŁ KOŃCÓWKI:  
miedź cynowana

TERMINAL MATERIAL:  
tinned copper

Artykuł Code	Przekrój Section		Do śruby For screw		W1	L1	L2	L3	L4	D1	D2	D3		
	mm <sup>2</sup>	(AWG)	ø mm	Stud size										
<b>011071</b>	1,5	(16)	3	# 4	8	16	5	5	4	3,5	1,9	3,2	100/100	
<b>011191</b>			4	# 8	8	16	5	5	4	3,5	1,9	4,2		
<b>011251</b>			5	# 10	8	16	5	5	4	3,5	1,9	5,2		100/1000
<b>011311</b>			6	# 12	10	18	5	6	5	3,5	1,9	6,3		100/100
<b>012191</b>	2,5	(14)	4	# 8	8	18	7	5	4	4	2,4	4,2	100/100	
<b>012251</b>			5	# 10	10	20	7	6	5	4	2,4	5,2		
<b>012311</b>			6	# 12	10	20	7	6	5	4	2,4	6,3		
<b>013190</b>	4	(12)	4	# 8	10	20	7	6	5	5,1	3,1	4,2	100/100	
<b>013250</b>			5	# 10	10	20	7	6	5	5,1	3,1	5,2		
<b>013310</b>			6	# 12	10	20	7	6	5	5,1	3,1	6,3		
<b>013370</b>			8	5/16	11	24	7	8,5	6,5	5,1	3,1	8,2		
<b>013191</b>	6	(10)	4	# 8	10	23	9	6	5	5,5	3,5	4,2	100/100	
<b>013251</b>			5	# 10	10	23	9	6	5	5,5	3,5	5,2		
<b>013311</b>			6	# 12	10	23	9	6	5	5,5	3,5	6,3		
<b>013371</b>			8	5/16	12	27	9	9	6	5,5	3,5	8,2		100/1000
<b>013431</b>			10	3/8	15	32	9	11	9	5,5	3,5	10,2	100/100	

**AKCESORIA • IZOLOWANE KAPTURKI**  
ACCESSORIES • INSULATED SLEEVES



MATERIAŁ ZOLACYJNY: PVC  
POZIOM SAMOGAŚNIĘCIA IZOLACJI:  
UL94 - V0  
TEMPERATURA ROBOCZA:  
maks. 85 °C

INSULATION MATERIAL: PVC  
INSULATION SELF-EXTINGUISHING  
GRADE: UL94 - V0  
OPERATING TEMPERATURE:  
85 °C max

Artykuł Code	Przekrój Section		L1	D1	D2	
	mm <sup>2</sup>	(AWG)				
<b>81001</b>	1,5	(16)	15	3,8	3,5	100/1000
<b>81002</b>	2,5	(14)	16,7	5	4	
<b>81006</b>	6	(10)	20,6	7	5,2	

**V0**