



SLIDE SWITCH SPECIFICATION

BSI-10 SERIES

Rev. 02
P : 1 / 1

1. Electrical Characteristics :

- 1-1 Rating : AC, DC 12V 0.5A ~ 24V 0.3A (Minimum current: 1mA)
- 1-2 Contact Resistance : Max 30mΩ
- 1-3 Insulation Resistance : Min 10,000 MΩ at DC 500V
- 1-4 Withstanding Voltage : 1min at AC 500V

2. Mechanical Characteristics :

- 2-1 Operating Force : 250 ± 150gf
- 2-2 Travel : 1.6mm
- 2-3 Insulator :
 - 2-3-1 Case : Glass Fiber resin
 - 2-3-2 Slide : Glass Fiber resin
- 2-4 Terminal : Nickel, Gold Plate

3. Life Test :

- 3-1 Test Condition : Operations at a rate of 15-20 cycles in 1 minute
 - 3-1-1 With load : 2,000 cycles
 - 3-1-2 Without load : 10,000 cycles
- 3-2 Operating Force : With +40%, -40% of Initial Value
- 3-3 Contact Resistance : Max 200mΩ

4. Environmental Characteristics :

- 4-1 Operating Temperature : -40°C to +85°C
- 4-2 Storage Temperature : -40°C to +85°C
- 4-3 Humidity Test :
 - 4-3-1 Test Conditions : Measured 1 hour after exposure to ambient
After 96 hours exposure at 40±2°C, 90-95%R.H
 - 4-3-2 Insulation Resistance : Min 100 MΩ at DC 500V
 - 4-3-3 Withstanding Voltage : 1 min at AC 250V

5. Solder Conditions :

- 5-1 Hand Solder : 3~4 sec. at 350°C
- 5-2 Wave Solder : 5 sec. at 260°C