




Specifications		
Nominal Voltage [V]	7.4	
Minimum capacity [mAh]	1850	
Typical capacity [mAh]	1950	
Charging voltage [V]	8.4	
Size [mm]	According to the drawing	
Weight [g]	100 ± 25	
Typical charge [mA]	370 (16 hrs)	
Rapid charge [mA]	1295 (temp. 20 °C)	
Standard continuous discharge current [mA]	3000 (temp. 20 °C)	
Charge temperature	Typical	0 °C do 45 °C
Discharge temperature	Continuous	-20 °C do 60 °C
Storage temperature	Recommended	-20 °C do 35 °C

LABEL: 50x30mm


 Li-Ion


CGA 103450/2S1P
WARNING!!!


 Li-Ion

Do not throw or hit. Do not heat or burn. Do not shortcircuit.
 Do not disassemble. Do not immerse in liquids
 Comply with the operating conditions.
 Do not charge at temperatures below 0 deg. C
 Discharge temperature -20 deg. C to 60 deg C

nominal voltage 7.2V	max discharge 3A
nominal capacity 1.95Ah	max charge 1.2A
nominal energy 14.04Wh	847B23620160023

Material/ Material:	Scale/ Skala: 1:1	Format/ Format arkusza: A3	Weight/ Masa:	Sheet/ Arkusz: 1/1	Version/ Wersja: 2
Finishing/ Wykończenie:	Date/ Data:				Revision/ Rewizja: B
Designed by/ Konstruował: J.Paliwoda					
Checked by/ Sprawdził:					Index WT:
Approved by/ Zatwierdził:					
Update/ Aktualizował: J. Dadacz	Update/ Data aktualizacji: 2016-09-29	Date of implementation/ Data wykonania: 2014-02-05	Product reference/ Nazwa: CGA103450/2S1P 2S1P CGA103450A - 847 v.2B	Docum. number/ Nr rysunku: 847.00.00.2B	