

REVISION RECORD		H		
REV	ECN	DESCRIPTION	DRFT	DATE

  

**Technical characteristics:**

**Specifications**  
 DIN EN 60 664-1  
 DIN EN 61 984  
 Approvals:

**Inserts**

- Number of contacts :15+PE
- Rated Current :10A
- Rated Voltage :250V
- Pollution degree :3
- Rated impulse voltage :4kv<sub>u</sub>
- Insulation resistance :≥10Ω
- Material:Polycarbonate
- Colour:RAL 7032(Light grey)
- Rated voltage acc.to UL/CSA:600V
- Limiting temperatures :-40℃~+125℃
- Flammability acc.to UL94:V0
- Mechanical working life (mating cycles) :≥500

**Contacts**

- Material:Copper alloy
- Surface:hard-silver plated
- Contact resistance :≤3mΩ
- Terminal :Crimp terminal
- Wire gauge :0.14-2.5mm<sup>2</sup> (AWG 26-14)
- Stripping length :6-8mm
- Rohs Compliance

Note:Crimp contact pins should order separately

  
  

PART NO: /		NINGBO DEGSON ELECTRICAL CO., LTD	
APPD: <i>MJS 2016.8.26</i>	NAME: 宁波高松电子有限公司		
CHKD: <i>LJM 2016.8.25</i>	DD-015-MC		
DRFT: Mr. Yang 2016.07.25	TITLE: CUSTOMER DRAWING		REV: DO-1
THIRD ANGLE PROJECTION		DRAWING NO: DD-015-MC-E01	SHEET 1/1
		DO NOT SCALE DRAWING	SCALE 1.5:1

DETACHED LISTS