

# DIGITUS®

## Professional

### DIGITUS® Line Interactive UPS DN-170015-1 1500VA/900W



- ✓ 4 Ways European output
- ✓ 2~6ms transfer time(10ms max)
- ✓ Fast Charge (4 hours 90%)
- ✓ LED monitor
- ✓ Backup time 30~40mins
- ✓ USB port & Software support

#### Abstract

DIGITUS® Line Interactive UPS DN-170015-1, 4ways European output 1500VA 900W

Input 160~290V AC Output 230V AC +/-10%

LED monitor. Software & USB port Supports Windows® 2000/2003/XP/Vista/2008/7/8, Linux, Unix, MAC

High performance protection for your business and office computer systems against data loss and damage

#### Features

- Capacity 1500VA/900W
- Input: 160~290V AC Output 230V AC +/-10%
- Typical 2-6 ms(10 ms max) Transfer Time , Charging Time 4-6 hours recover to 90% capacity. Simulated Sine Wave
- BATTERY 12 V/7 AH x 2
- Sound alarm. Overload, discharge, and overcharge protection
- Dimension (DxWxH) 397X146X205 mm Net Weight 11.1Kg
- USB Supports Windows® 2000/2003/XP/Vista/2008/7/8, Linux, Unix, MAC

#### Product Overview

DIGITUS® Line Interactive UPS with Compact size, excellent microprocessor control guarantees high reliability

Boost and buck AVR for voltage stabilization, Auto restart while AC is recovering

Off-mode charging and cold start function

DIGITUS® is made for high demand IT-Infrastructure Solutions – designed and developed on highest standard in Germany.



## DIGITUS<sup>®</sup> Line Interactive UPS DN-170015-1 1500VA/900W

### Part Number Information

- DN-170013-1 Line Interactive UPS, 2ways European output. 600VA 360W, Input 160~290V AC, Output 230V AC +/-10%
- DN-170014-1 Line Interactive UPS, 4ways European output 1000VA 600W, Input 160~290V AC, Output 230V AC +/-10%.  
Software & USB port, LED monitor
- DN-170015-1 Line Interactive UPS, 4ways European output 1500VA 900W, Input 160~290V AC, Output 230V AC +/-10%.  
Software & USB port, LED monitor

DIGITUS<sup>®</sup> is made for high demand IT-Infrastructure Solutions – designed and developed on highest standard in Germany.