

# DIGITUS Professional VGA Splitter 350MHz, 2-Port

DS-41100  
EAN 4016032325024



## Video Splitter 1 PC, 2 Monitors, 350 MHz 350 MHz, HDSUB 15/M - 2 X HDSUB 15/F, Max. Res. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

**Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshows, or in-store displays**

- Video bandwidth: 350MHz

- Max. resolution: 2048x1536p @60Hz
- DDC, DDC2, DDC2B support
- Cascadable (max. 64)
- Metal housing for better EMI shielding
- Max. transmission distance: 75m
- Video IN/OUT: HD DSUB, 15-pin, jacks

### Lieferumfang

- VGA Splitter 350 MHz, 2-Port
- Power supply
- Manual

Logistische Daten						
	Anzahl (Stück)	Gewicht (kg)	Tiefe (cm)	Breite (cm)	Höhe (cm)	cm <sup>3</sup>
Karton-VPE	10	7,50	32,00	28,50	32,00	29.184,00
Innen-VPE	1	0,75	6,00	25,00	15,00	2.250,00
Einzel-VPE	1	0,75	6,00	25,00	15,00	2.250,00
Netto einzeln ohne VP	1	0,47	9,20	13,50	5,00	621,00



**Weitere Anwendungsbilder:**

