

DIGITUS Professional VGA Splitter 500MHz, 2-Port

DS-41110
EAN 4016032323808



Video Splitter 1 PC, 2 Monitors 500 MHz, HDSUB 15/M - 2 X HDSUB 15/F Max. Res. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshows, or in-store displays

- Enables to split a video-signal from a PC onto 2 monitors, or other video output devices

- Video bandwidth: 500MHz
- Max. resolution: 2048x1536p @60Hz
- Max. transmission distance: 75m
- Cascadable (max. 64)
- Metal housing for better EMI shielding
- DDC, DDC2, DDC2B support
- Video IN/OUT: HD DSUB, 15-pin, jacks

Lieferumfang

- VGA Splitter 500 MHz, 2-Port
- Power supply
- Manual

| Logistische Daten | | | | | | |
|-----------------------|----------------|--------------|------------|-------------|-----------|-----------------|
| | Anzahl (Stück) | Gewicht (kg) | Tiefe (cm) | Breite (cm) | Höhe (cm) | cm ³ |
| Karton-VPE | 10 | 21,00 | 27,00 | 55,00 | 49,00 | 72.765,00 |
| Innen-VPE | 1 | 2,10 | 6,50 | 25,00 | 15,00 | 2.437,50 |
| Einzel-VPE | 1 | 2,10 | 6,50 | 25,00 | 15,00 | 2.437,50 |
| Netto einzeln ohne VP | 1 | 0,48 | 9,00 | 13,50 | 4,00 | 486,00 |



Weitere Anwendungsbilder:

