

DIGITUS Professional VGA Splitter 350MHz, 2-Port

DS-41120-1
EAN 4016032323839



**DIGITUS VGA Splitter, 2port, plastic housing 350 MHz, HDSUB 15/M
-> 2x HDSUB 15/F Max. Res. 1920x1080p**

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshows, or in-store displays

- Plastic housing

- Video bandwidth: 350MHz
- Max. resolution: 1920x1080p
- DDC, DDC2, DDC2B support
- Cascadable (max. 64)
- Max. transmission distance: 75m
- Video IN/OUT: HD DSUB, 15-pin, jacks

Lieferumfang

- VGA Splitter 350 MHz, 2-Port
- Manual

| Logistische Daten | | | | | | |
|-----------------------|----------------|--------------|------------|-------------|-----------|-----------------|
| | Anzahl (Stück) | Gewicht (kg) | Tiefe (cm) | Breite (cm) | Höhe (cm) | cm ³ |
| Karton-VPE | 60 | 8,40 | 28,50 | 33,00 | 32,00 | 30.096,00 |
| Innen-VPE | 1 | 0,14 | 3,20 | 13,50 | 10,50 | 453,60 |
| Einzel-VPE | 1 | 0,14 | 3,20 | 13,50 | 10,50 | 453,60 |
| Netto einzeln ohne VP | 1 | 0,09 | 6,50 | 6,50 | 2,00 | 84,50 |



Weitere Anwendungsbilder:

