

# DIGITUS Professional VGA Splitter 350MHz, 4-Port

DS-42100  
EAN 4016032323785



## Video Splitter 1 PC, 4 Monitors 350 MHz, HDSUB 15/M - 4 X HDSUB 15/F Max. Res. 2048x1536p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

**Provides simultaneous display on four different monitors - Perfect for classrooms, tradeshows, or in-store displays!**

- Video bandwidth: 350MHz

- Max. resolution: 2048x1536p @60Hz
- DDC, DDC2, DDC2B support
- Cascadable (max. 64)
- Metal housing for better EMI shielding
- Max. transmission distance: 75m
- Video IN/OUT: HD DSUB, 15-pin, jacks

### Lieferumfang

- VGA Splitter 350 MHz, 4-Port
- Power supply
- Manual

Logistische Daten						
	Anzahl (Stück)	Gewicht (kg)	Tiefe (cm)	Breite (cm)	Höhe (cm)	cm <sup>3</sup>
Karton-VPE	10	27,00	49,00	55,00	49,00	132.055,00
Innen-VPE	1	2,70	14,80	25,00	6,00	2.220,00
Einzel-VPE	1	2,70	14,80	25,00	6,00	2.220,00
Netto einzeln ohne VP	1	0,00	0,00	0,00	0,00	0,00



**Weitere Anwendungsbilder:**

