



**Contactor, 4p, 4kW/400V/AC3**



Powering Business Worldwide™

**Part no.**

**DILEM4-G(220VDC)**

**Article no.**

**215658**

**Catalog No.**

## Delivery programme

Basic function  
Basic function accessories

Busbar  
Busbar for miniature circuit-breaker  
Busbar for residual-current circuit-breakers  
Busbar for combined residual-current/power circuit-breaker  
3-phase + auxiliary contact  
EVG

Type  
Product range

## Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss8-27-37-13-06 [ACN992007])

Number of phases		3
Suitable for number of devices		4
Pitch dimensions	mm	0
Cross section	mm <sup>2</sup>	10
Length	mm	210
Rated permanent current I <sub>u</sub>	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I <sub>q</sub>	kA	25
Max. rated operation voltage U <sub>e</sub>	V	500
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		Yes