



Control switch, 3p, Ie=12A, FS 0-1, 45°, momentary,
48x48 mm, flush mounting

EATON

Powering Business Worldwide™

Part no. **T0-2-8206/E**
Article no. **215640**
Catalog No.

Delivery programme

Basic function
Basic function accessories

Busbar
Busbar for miniature circuit-breaker
Busbar for residual-current circuit-breakers
Busbar for combined residual-current/
power circuit-breaker
Three-phase
EVG

Type
Product range

Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar
(ecl@ss8-27-37-13-06 [ACN992007])

Number of phases		3
Suitable for number of devices		2
Pitch dimensions	mm	0
Cross section	mm ²	10
Length	mm	105
Rated permanent current I _u	A	63
Type of electric connection		Fork
Insulated		Yes
Rated surge voltage	kV	4
Conditioned rated short-circuit current I _q	kA	25
Max. rated operation voltage U _e	V	500
Rated short-time withstand current I _{cw}	kA	0
Suitable for devices with N-busbar		No
Suitable for devices with auxiliary switch		No