

Mechanical characteristics
cable group

interface dimensions acc. to assembly code
 centre conductor
 outer conductor
 mating life
 coupling torque

Components
 centre contact
 outer contact
 other metal parts
 insulator
 gasket

Electrical characteristics
 impedance
 frequency
 return loss
 intermodulation

working voltage
 voltage proof
 insulation resistance
 contact resistance
 centre contact
 outer contact

Environmental
 operating temp.
 protection class
 RoHS compliant

Mechanische Eigenschaften
Kabelgruppe

Steckgesicht nach Montageanleitung
 Innenleiter
 Außenleiter
 Steckzyklen
 Kupplungsdrehmoment

Bauteile
 Innenkontakt
 Außenkontakt
 sonstige Metallteile
 Isolierung
 Dichtung

Elektrische Eigenschaften
 Wellenwiderstand
 Frequenz
 Rückflussdämpfung
 Intermodulation

Betriebsspannung
 Prüfspannung
 Isolationswiderstand
 Durchgangswiderstand
 Innenkontakt
 Außenkontakt

Umgebung
 Betriebstemperatur
 Schutzklasse
 RoHS konform

G21: 5128 1/2"-LD Eupen, Flexline 1/2" R Leoni, HFC 12D LS Cable, HPL 50-1/2 Acome, LCF 50A Andrew, RFA 1/2"-50 Draka, RFX 1/2"-50 Draka, SUCOFEEED_1/2 Huber+Suhner



IEC 61169-54
 B90
 clamp / klemm
 clamp / klemm
 >100
 5 Nm

Materials / Material
 copper alloy / Kupferleg.
 brass / Messing
 brass / Messing
 Topas (COC)
 silicone / Silikon

Finish / Oberfläche
 Cu2Ag5
 Ag2CuSnZn0,5; Cu2Ni5
 Cu2Ni5; CuSnZn3

50 Ω
 0 - 3 GHz
 typ.: 1 GHz - 40 dB; 2 GHz - 36 dB; 3 GHz - 35dB
 IMP 3rd order -155 dBc
 (2x43 dBm (20 W)unmodulated test tones)
 ≤ 1,0 kV_{eff} / 50 Hz
 2,5 kV_{eff} / 50 Hz
 > 5 GΩ
 ≤ 1,0 mΩ
 ≤ 0,5 mΩ

-40°C / +85°C
 IP 68 (IEC 60529)
 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight (g)	
			gez./ drawn	25.02.2015	BJ		
			gepr./ appr	03.03.2015	KL	ca./approx. 96	
			Maßstab/ scale	Benennung/ title			
			1:1	4.3-10 Straight Plug Screw SIMFix® Pro 4.3-10 Kabelstecker Screw SIMFix® Pro			
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.		 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1
			K	J01440A0007			
			Ersatz für/ replaces	EWB40086-00			