

# KMK-PA-MB counternut with collar



## KMK-PA-MB

The counternut made of polyamide.  
The counternut with collar has a bigger sealing area - sealing with an additional O-ring will be simplified.

## Application

- Plant and machine construction
- Automation technology
- Vehicle construction and shipbuilding
- Installation technology
- Control cabinet construction

## Material

Polyamide PA 6


- halogen-free
- phosphor-free
- silicone-free
- cadmium-free

## Note

UV-resistant (RAL 9005).

## Technical data

Temperature range: -40°C up to +100°C



## Dimensions

G Thread size inside  
SW Spanner size

## metric thread

Part no. RAL 7035	Part no. RAL 7001	Part no. RAL 9005	Size Mettr.	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
97816	94260	98163	M12 x 1,5	18	100	o. r.	o. r.	o. r.
97817	94261	98164	M16 x 1,5	22	100	o. r.	o. r.	o. r.
97818	94262	98165	M20 x 1,5	26	100	o. r.	o. r.	o. r.
97819	94263	98166	M25 x 1,5	32	100	o. r.	o. r.	o. r.
97820	94264	98167	M32 x 1,5	41	100	o. r.	o. r.	o. r.
97821	94265	98168	M40 x 1,5	50	50	o. r.	o. r.	o. r.
97822	94266	98169	M50 x 1,5	60	50	o. r.	o. r.	o. r.
97823	94267	98170	M63 x 1,5	75	25	o. r.	o. r.	o. r.

## PG thread

Part no. RAL 7035	Part no. RAL 7001	Part no. RAL 9005	Size PG	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
90710	94250	96458	7	19	100	o. r.	o. r.	o. r.
90711	94251	96228	9	22	100	o. r.	o. r.	o. r.
90712	94252	96459	11	24	100	o. r.	o. r.	o. r.
90713	94253	96460	13,5	27	100	o. r.	o. r.	o. r.
90714	94254	96461	16	30	100	o. r.	o. r.	o. r.
90715	94255	96176	21	36	100	o. r.	o. r.	o. r.
90716	94256	96177	29	46	50	o. r.	o. r.	o. r.
90717	94257	96462	36	60	25	o. r.	o. r.	o. r.
90718	94258	96463	42	65	25	o. r.	o. r.	o. r.
90719	94259	96464	48	70	25	o. r.	o. r.	o. r.

## NPT thread

Part no. RAL 7035	Part no. RAL 7001	Part no. RAL 9005	Size NPT	Spanner size mm	Unit	Net EUR/100 items at a purchase of		
						up to 100	101 - 500	501 - 1000
97317	90870	90875	3/8"	22	100	o. r.	o. r.	o. r.
97316	90871	90876	1/2"	27	100	o. r.	o. r.	o. r.
97315	90872	90877	3/4"	33	100	o. r.	o. r.	o. r.
98366	90873	90878	1"	47	50	o. r.	o. r.	o. r.

Dimensions and specifications may be changed without prior notice.

o. r. = on request