



**Type:** 57671 **Systems to charge:** Ni-MH  
**Designation:** LCD Multi Charger **Cell sizes:** AAA, AA  
**Cell Configurations:** AAA, AA 2 / 4 / 6 / 8 pcs.

Dimensions:	Charger:	AC/DC-Adapter:
Lenght:.....	167 ± 1 mm	76.4 ± 1 mm
Widht:.....	106 ± 1 mm	43.2 ± 1 mm
Height:.....	32 ± 1 mm	30 ± 1 mm
Weight:.....	198 ± 1 g	111 ± 1 g

**Charging methods:** AC adaptor input(200-240V 50Hz) 5.4V 3A:

AA:..... Current: 450mA ± 10%  
 AAA:..... Current: 200 mA ± 10%  
 5V USB:..... Current:1000 mA ± 10%

**Housing:**

Housing Material:..... PA765  
 Casing color:..... Black

**Indications: LCD display**

AAA, AA,cell mix:..... 1st bar flashing <1.39V  
 1st bar solid and 2nd bar flashing <1.41V  
 AAA ,AA,cell mix:..... 1st and 2nd bars solid and 3th bar flashing <1.45V  
 AAA ,AA,cell mix:..... 1st, 2nd and 3th bars solid and 4th bar flashing <1.54V  
 AAA ,AA,cell mix:..... All bars are solid : -dv

**Protective Functions:**

Reverse protection Mechanical arrangement  
 Short circuit protection No current, LCD flash

**Power:**

Primary:..... 200-240V AC 50 Hz  
 Secondary:..... 2.8V

**Cut off criteria:**

Ni-MH standard cells:... Timer: 6.5 hours + / - 1 hour for AA/AAA  
 -DV: 10mV +/- 2mV / Channel, function immediately  
 Vmax: >1.65V

**No publication or circulation of data to third parties without consent of VARTA Consumer Batteries**