



ul. Konstytucyjna 79/81  
95-200 Pabianice  
tel/fax 48 42 2270971 POLAND  
e-mail: fif@fif.com.pl

## LK-714 SIGNAL LAMP two ability type



5 9 0 8 3 1 2 1 5 9 2 2 5 9

[www.fif.com.pl](http://www.fif.com.pl)

F&F products are covered by an 24 months warranty from date of purchase

### PURPOSE

The light signal LK-714 is used for optical signaling circuits or states listed receivers, such as closed - open; work - break, etc.

### FUNCTIONING

The position of controlled circuit or the receiver is indicated by lighting the appropriate LEDs connected in parallel to this circuit or the receiver.

### ATTENTION

Where the point of connection to the network lights the fuse is installed under-current equal to or greater than 25A a circuit to connect the lamps care fuse should be no more than 6A.


### ASSEMBLY

1. Check the sequence of phases
2. Take OFF the power.
3. Put on indicator on the rail in the switchgearbox.
4. Connect to system with marks..

### TECHNICAL DATA

Current load	2×1,7mA
indicator	LED red-green
power consumption	2×1,1W
connection	screw terminals 2,5mm <sup>2</sup>
working temperature	-25+50°C
dimensions	1 module (18mm)
fixing	on rail TH-35

### WIRING DIAGRAM



A090722