


## Product Description

Maximum reliability; Optimal strain relief; Large, variable clamping ranges



## Application range

- In areas with high demands on special mechanical and chemical stability.
- Chemical industry
- Measurement and control technology
- Machine and apparatus construction
- Plant engineering

## Benefits

- Maximum reliability
- Optimal strain relief
- Large, variable clamping ranges

## Design

- PG connection thread

## Note

- Counter nut to be used SKINDICHT® SM
- For suitable accessories see SKINTOP® accessories PG



Technical Data

**Caution**

Installation dimensions and tightening torques see Appendix T21

**Material**

Body: Nickel plated brass Insert: Polyamide Seal: CR O-ring: NBR

**Degree of protection**

IP 68 - 5 bar

**Range of temperature**

-30°C up to +100°C

Article List

Part number	Part designation / size	Clamping range ØF mm	SW mm	Overall length C mm	Thread length D mm	Pieces / PU
SKINTOP® MS						
52015700	MS 7	2 - 6,5	14	25.0	5.0	100
52015710	MS 9	4 - 8	17	29.0	6.0	100
52015720	MS 11	4 - 10	20	32.0	6.0	50
52015730	MS 13,5	5 - 12	22	34.0	6.5	50
52015740	MS 16	8 - 14	24	35.0	6.5	50
52015750	MS 21	11 - 18	30	40.0	7.0	25
52015760	MS 29	16 - 25	40	48.0	8.0	25
52015765	MS 36	19 - 32	50	62.0	15.0	10
52015766	MS 42	28 - 38	57	62.0	15.0	5
52015767	MS 48	34 - 44	64	62.0	15.0	5

**Footnote:**

Photographs are not to scale and do not represent detailed images of the respective products.