

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINTOP® GMP-HF-M</b>	14.11.2013

Halogen-free  
 Extremely flame-retardant according to UL 94 V0  
 Self-extinguishing, no dripping



Halogen-free



Assembly time



Temperature-resistant



Variety of approval certifications

#### Info

Cable gland for railway applications- Fire protection on railway vehicles Approval according to DIN EN 45545-2:2013

#### Application range

For locking SKINTOP® cable glands in boreholes without thread.

Airports

Tunnel construction

Underground railways

Public buildings

#### Design

Metric connection thread acc. to EN 50262

#### Note

Designed for use with SKINTOP® ST-HF-M

#### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

#### Technical Data

Colour delivered: Light grey (RAL 7035)

Material: Polyamide UL 94V-0 - halogen-free

Temperature range: -20°C to +100°C

Product Management	Document: LAPP_PRO26780EN.pdf	1 / 2
--------------------	-------------------------------	-------



**SKINTOP® GMP-HF-M**

14.11.2013

Part number	Article designation / size	SW (mm)	PU
SKINTOP® GMP-HF-M			
53119200	12 x 1,5	17	100
53119210	16 x 1,5	22	100
53119220	20 x 1,5	27	100
53119230	25 x 1,5	34	100
53119240	32 x 1,5	41	100
53119250	40 x 1,5	50	25
53119260	50 x 1,5	60	25
53119270	63 x 1,5	75	25