

## LED light bar OPBxx3014-03012WO - PRODUCT DATASHEET



<b>Voltage</b>	12 V DC
<b>Power</b>	7,2 W/m
<b>Luminocity</b>	690 lm/m
<b>Qty LED</b>	60 LED/m
<b>Distance between LED</b>	33,3 mm
<b>Can be cut into section</b>	10 cm

Powered by



### Basic information:

- PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY
- PROFESSIONAL PCB MOUNTING, ONLY BRAND-NAME LED DIODES (OSRAM)
- MODULES CAN BE SPLIT INTO 10 CM SECTIONS (3LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 5M)

### Typical application:

- UTILITY, DECORATIVE LIGHTING
- CEILING, WALL, NICHE, SHELF, PASSAGEWAYS BACKLIGHTING
- ADVERTISING (SIGNBOARDS): SHOP, MUSEUM, TARDE FAIRS EXPOSITIONS ETC.
- KITCHEN WORKTOPS LIGHTING

### Explanation:

- "xx" - COLOR DESIGNATION E.G. WH, WN AND WW



**UWAGA**  
ZACHOWAĆ OSTROŻNOŚĆ  
ELEMENTY WRAZLIWE  
NA WYŁĄDZOWANIE  
ELEKTROSTATYCZNE




PRODUKT WYKONANY  
Z PODZESPOŁÓW  
ZGODNYCH Z NORMĄ  
RoHS



**IP20**

### Additional Information

Color	Cool white WH	Neutral white WN	Warm white WW
<b>Voltage</b>		12 V DC	
<b>Power</b>		7,2 W/m	
<b>Power of single LED</b>		0,24 W	
<b>Current</b>		0,6 A/m	
<b>Luminocity</b>	690 lm/m	690 lm/m	670 lm/m
<b>Qty LED</b>		60 LED/m	
<b>Distance between LED</b>		33,3 mm	
<b>Can be cut into section</b>		10 cm	
<b>Width</b>		10 mm	
<b>Height</b>		3 mm	
<b>Color temperature / Wavelength scope</b>	5000 K	4000 K	3000 K
<b>Beam angle</b>		120°	
<b>Color rendering index (Ra)</b>		80	
<b>Operating temperature</b>		-25 - +60°C	
<b>Storage temperature</b>		-40 - +80°C	
<b>IP degree</b>		IP20	



In spite of all our efforts, we do not guarantee, that technical data doesn't include any mistakes or defects, which can't be basis of any claiming. Figures and pictures are for illustration only and can be different from authentic appearance of product.