


LED light bar OPBxx3014-06012WO - PRODUCT DATASHEET



Voltage	12 V DC
Power	14,4 W/m
Luminocity	1380 lm/m
Qty LED	60 LED/m
Distance between LED	16,6 mm
Can be cut into section	5 cm

Powered by



Basic information:

- PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY
- PROFESSIONAL PCB MOUNTING, ONLY BRAND-NAME LED DIODES (OSRAM),
- MODULES CAN BE SPLIT INTO 5 CM SECTIONS (3LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 5M)

Typical application:

- UTILITY LIGHTING
- CEILING, WALL, NICHE, SHELF, PASSAGeways BACKLIGHTING
- ADVERTISING (SIGNBOARDS): SHOP, MUSEUM, TARDE FAIRS EXPOSITIONS ETC.
- KITCHEN WORKTOPS LIGHTING

Explanation:

- "xx" - COLOR DESIGNATION E.G. WH, WN AND WW



UWAGA
ZACHOWAĆ OSTROŻNOŚĆ
SŁABIEJ WYŚWIETLANIE
NA WYŁĄCZANIU
ELEKTROSTATYCZNE




PRODUKT WYKONANY
Z PODZESPOŁÓW
ZGODNYCH Z NORMĄ
RoHS



IP20

Additional Information

Color	Cool white WH	Neutral white WN	Warm white WW
Voltage		12 V DC	
Power		14,4 W/m	
Power of single LED		0,24 W	
Current		1,2 A/m	
Luminocity	1380 lm/m	1380 lm/m	1340 lm/m
Qty LED		60 LED/m	
Distance between LED		16,6 mm	
Can be cut into section		5 cm	
Width		10 mm	
Height		3 mm	
Color temperature / Wavelength scope	5000 K	4000 K	3000 K
Beam angle		120°	
Color rendering index (Ra)		80	
Operating temperature		-25 - +60°C	
Storage temperature		-40 - +80°C	
IP degree		IP20	



In spite of all our efforts, we do not guarantee, that technical data doesn't include any mistakes or defects, which can't be basis of any claiming. Figures and pictures are for illustration only and can be different from authentic appearance of product.