

BLBT100



LIGHT GARAGE EQUIPMENT

- Dual laser head light tester
- Laser alignment visor & pointer
- Standard and XENON headlights
- Digital luxometer
- Anti tilting robust base with 4 wheels for easy manoeuvring
- Height setting easy mechanism with block
- Working range:
 - □ Min. height: 240 mm
 - □ Max height: 1 400 mm
- Swivel bar allows 360° rotation of the body of the headlight over the axis of the bar which makes very appropriate for mounting over rail tracks
- Optional rail track BLBT100AC1
- CE and NFR63-801 approved

| | 731415 | | \$ mm | kg |
|---------|---------|---|--------------|------|
| BLBT100 | 0179015 | 1 | 330x1700x630 | 40.5 |

1419-MD



LIGHT GARAGE EQUIPMENT

- Magnetic dish 150 mm
- For easy storage of bolts, nuts and tools whilst working
- Magnetic rubber protected base will attach to any magnetic surface

| | 731415 | | ← L mm | Ø mm | g |
|---------|---------|----|----------------------|---------|-----|
| 1419-MD | 8277352 | 36 | 150 | 150 | 300 |

2535F



LIGHT GARAGE EQUIPMENT

- Handle developed according to the scientific ERGO[™] process
- Handle: 3-component handle, for maximum comfort and force transmission
- Blade finish: Chrome plated and polished
- 2535F1: Neodym magnet Ø 10 mm, capacity 1 kg/35 oz
- 2535F3: Neodym magnet Ø 17 mm, capacity 3 kg/106 oz

| | 731415 | | Ø mm | → mm | ★ | mm | g |
|--------|---------|---|---------|-------------|----------|-----|-----|
| 2535F1 | 1064495 | 1 | 10 | 413 | 36x122 | 535 | 150 |
| 2535F3 | 0180233 | 1 | 17 | 413 | 36x122 | 535 | 170 |

