



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

RECOMMENDED
CABLE STRIPPING DIM'S

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
11	NUT		NOTE 1	NOTE 3	1 B5291-14
10	FERRULE	COPPER		NOTE 3	1 FR-648/533X127C
9	WASHER		NOTE 2	NOTE 3	1 WS-128/9X08
8	RING	DELTRIN		NATURAL	1 T50000-6-A
7	RETAINER RING		NOTE 1	NOTE 3	1 B50000-5
6	GASKET	RUBBER		RED	1 GS-105/8X15
5	CONTACT PIN		NOTE 1	NOTE 4	1 B5091-6-50
4	INSULATOR	DELTRIN		NATURAL	1 B50002-3-50
3	BARREL		NOTE 1	NOTE 3	1 B5091-3-46/31
2	HOUSING		NOTE 1	NOTE 3	1 B5091-2
1	SHELL		NOTE 1	NOTE 3	1 T50000-1-B

DIMENSIONS ARE IN MILLIMETERS				PART NO. T1112A1-ND3G-1-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED	DATE 10-11-01'
				CHECKED	DATE 10-11-01'
				DRAWN	DATE 10-11-01'
				SCALE 3/1	ISSUE A

Amphenol	
TITLE TNC R/A CRIMP PLUG (FOR RG-58/U,58C/U)	
DRAWING NO. KJ-T1112A1-ND3G-58U-50	
ITEM NO.	