Technical Data







SOLID MARKER is a stick of solid paint pigments ideal for marking rough surfaces such as concrete. The tip can be sharpened for more precise marks.

FEATURES

- Solid paint stick
- Long-lasting marks
- · Good visibility
- UV resistant
- Excellent water resistance
- Available in 2 colours (Yellow and White)

APPLICATIONS

- Steel construction
- Ship repair
- Civil engineering

TECHNICAL DATA

Appearance Coloured wax

Density $>1g/cm^3$ (@20°C)

Temperature range -46°C to 66°C

Maximum Operational Temp. 100°C

Packaging 12 markers

DIRECTIONS FOR USE

Use directly on to surface that requires marking. Tip may be sharpened for more precise marks.

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 48 months with correct storage.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200 Fax: +44 (0) 1278 425644

Web: www.ambersil.com E-mail: sales.uk@crcind.com

Version: 1 Created: June 2012