



CRC BRAKLEEN

Ref. : 10126-10128

1. GENERAL DESCRIPTION

Powerful cleaner/degreaser for brake and clutch parts.

A non-chlorinated solvent blend, formulated to quickly and safely remove brake fluid, grease, oil and other contaminants from brake and clutch parts.

Brakleen helps brakes last longer and perform better.

2. FEATURES

- Effectively removes brake fluid, grease, oil and hardened deposits.
- Degreases instantly.
- Reduces disc-brake squeal and clutch chatter.
- Can be applied without disassembly, saving time and reducing maintenance costs.
- Evaporates quickly.
- Leaves no residue.
- Low surface tension gives excellent penetration and ensures superior dissolving and degreasing properties.
- Stable, non-staining and non-corrosive to metals.
- Safe on most plastics, coatings and rubbers (test prior to use).
- Aerosol is equipped with a 360° (upside-down) spray valve and extension tube for added convenience.
- Aerosol is pressurized with CO₂ propellant, giving an active product content of over 95%.

3. APPLICATIONS

Perfect for cleaning and degreasing:

- Brake linings
- Drums
- Cylinders
- Brake shoes
- Disc brake pads
- Discs
- Wedge brakes
- Springs
- Calipers
- Clutch discs
- Equipment
- Parts and tools



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





CRC BRAKLEEN

Ref. : 10126-10128

4. DIRECTIONS

- Spray liberally and allow excess to run off. Air dry or dry with absorbent cloth. Repeat if necessary.
- Use extension tube for hard-to-reach areas.
- After application, re-lubricate with CRC 5-56 if necessary.
- Check plastics and rubber compatibility before use. Do not use on sensitive electronics. Use one of CRC's precision cleaners for these applications.
- Use with adequate ventilation. Do not use on energized equipment. Allow to dry thoroughly and vent before reactivating system.
- A safety data sheet (MSDS) according to EU directive 91/155/EEC and amendments is available for all CRC products.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: colorless liquid, typical odor
Specific gravity @ 20°C	: 0,72
Boiling range	: 55-120 °C
Vapor density (vs. air = 1)	: 3
Freezing point	: < -30°C
Evaporation rate (vs. ether = 1)	: 2,8
Flash point (closed cup)	: < 0°C
Surface tension @ 20°C, est.	: 21 mN/m
Plastics compatibility	: to be checked (*)
Non-volatiles	: none

6. PACKAGING

Aerosol:	12 x 500 ml
Bulk:	4 x 5 l
	20 l
	60 l

* Sensitive plastics (e.g. polystyrenes and polycarbonates,) need to be checked, particularly when thermal or mechanical stress is involved.

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10126-10128 03 0900 03

Date : 21 May 2013



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

