



Art No. UA0149

USB3.0 4-Port Hub

The UA0149 is very well shielded owing to its metallic casing and as such is the optimum solution for an industrial use. It can be mounted below the table or at the wall. This creates order at the work place. The power pack contained in the scope of supply provides for extra power with current hungry USB devices. Also, diagnostic LEDs provide port status for each port and power status.

Features:

- Compliant to USB3.0/2.0/1.1 Specification
- Supports USB3.0 High-Speed up to 5Gbps
- 1 x up-stream port and 4 x down-stream
 LED status indicator ports support
- Connects up to 127 USB devices
- Equipped with over-current Detection & Protection
- With external power adapter (5V, 3.5A)
- Metal housing with mounting rack
- Plug & Play
- Supports Windows XP/Vista/7

Technical Specifications:

Dimensions (W×H×D)	117x20×45 mm	
Weight	130g	
Power Adapter	100-240V AC, 50-60Hz, 3500mA	
Input Voltage	Without Power Adapter	5V DC, 500 mA
	With Power Adapter	5V DC, 3500 mA
Cable Length	0.6m	
Operating Temperature	-5°C to 45°C	
Storage Temperature	-10°C to 60°C	

Package Content:

- 1 x USB3.0 Cable
- 1 x Power Adapter
- 1 x User Manual

Packaging Information:

- 1 x 4-Port USB HUB Packing Dimension: 170x117x60 mm
 - Packing Weight: 0.4kg
 - Carton Dimension: 380x300x300 mm
 - Carton Q'ty: 25pcs
 - Carton Weight: 9kg





