



DRAWING

J1	1	1
	2	2
	3	3
SHELL	4	4
	5	5
J2	1	6
	2	7
	3	8
SHELL	4	9
	5	5

- 1.CABLE:UL2725,USB CABLE,28AWG(7/0.12mm)X1PAIRS
+24AWG(7/0.2mm)X2C,TIN COPPER
- SHIELD:AL-FDIL+7/0.1mmDRAIN WIRE+2X16/0.1mm
BRAID TIN COPPER
- JACKET:PVVC,DI:4.8mm±0.2mm,COLOR:GREY
- CONNECTOR:2 PCS USB A SOLDER FEMALE GOLD FLASH
- 3.HOOD:MOULDING TYPE,COLOR:GREY
- 4.1 PCS 10 PIN IDE FEMALE,COLOR:BLACK
- 5.1 PCS TUBE
- 6.FULL RDS Guideline
- 7.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

PART NO	USBAJ-2	SHEET NO	1	THIRD ANGLE PROJECTION
TITLE: 2 *USB A FEMALE TO 10P IDE FEMALE				
L:0.25M,UL2725,GREY COLOR				
DWN NO	D-USBAJ-2	SCALE	N.T.S	DRAWN BY & DATE
		SIZE	A4	CHECKED BY & DATE
		UNIT	mm	APPROVED BY & DATE
		<input checked="" type="checkbox"/> mm	<input type="checkbox"/> INCH	

