

UT200 Series
400-600A Digital Clamp Meters
UT203 UT204 UT204A

Introduction

Safety Rating

CAT II 600V

CAT III 300V

Certifications

CE

EN:61010-1

EN:61326-1

EN:61010-2-032

Specifications

Model		UT203	UT204	UT204A
AC Current (A)	40A/400A 40A/600A	±(2.5%+5)	±(2.5%+5)	±(2.5%+5)
DC Current (A)	40A/400A 40A/600A	±(2%+3)	±(2%+3)	±(2.5%+5)
AC Voltage (V)	4V/40V/400V/600V	±(1%+5)	±(1%+5)	±(1%+5)
DC Voltage (V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)	±(0.8%+1)
Resistance (Ω)	400Ω/4KΩ/40KΩ/400KΩ/4MΩ/40MΩ	±(1%+2)	±(1%+2)	±(1%+2)
Capacitance (F)	4nF/40nF/400nF/4μF/40μF/100μF			±(4%+3)
Frequency (Hz)	10Hz~1MHz 10Hz ~ 10MHz 10MHz	±(0.1%+3)	±(0.1%+3)	±(0.5%+3) Reference only
Temperature (°C)	-40 °C ~ 1000°C			±(2.5%+3)

Features

Display Count		3999	3999	3999
Auto Range		√	√	√
Jaw Capacity		28mm	28mm	28mm
True RMS			√	
Duty Cycle	0.1%~99.9%	√	√	
Diode		√	√	√
Auto Power Off		√	√	√
Continuity Buzzer		√	√	√
Low Battery Indication		√		√
Data Hold		√	√	√
Relative Mode		√	√	
MAX Mode				√
Setup		√	√	√
Input Impedance for DCV	Around 10MΩ	√	√	√

General Characteristic

Power	9V Battery (6F22)
LCD Size	35.6X 18mm
Product Color	Red and Grey
Product Net Weight	260g
Product Size	208mm X 76mm X30 mm
Standard Accessories	UT203/UT204 -Battery, Test Lead,Carrying Bag , UT204A -Battery, Test Lead,Carrying Bag, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)

Standard Carton Gross Weight	25Kg
------------------------------	------