

Datasheet

Art.No. 91.050.3251.0

Distributor GST15i5VA2A1HR W 2 WS

Distribution block GST15i5 to GST18i3 L2, 5- to 3-pole, 1 input GST18i5, 1 output GST15i5, 1 output GST18i3 L2, 250/400V/16A, color of coding: white



| | |
|------------|---------------|
| Art.No. | 91.050.3251.0 |
| EAN | 4049088037948 |
| Order unit | 1 pieces |

Approvals



Technical data

General

| | |
|-----------------------|----------------|
| Rated current | 16 A |
| Rated voltage | 250 V |
| Rated voltage 2 | 400 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Yes |
| Lockable | Yes |
| Marking of poles | 3, N, PE, 2, 1 |

Model

| | |
|---------------------------|---------------|
| Number of inputs | 1 |
| Number of outputs | 2 |
| Type of fastening | No |
| Degree of protection (IP) | IP20 |
| Type of distributor | h-distributor |

Material

| | |
|--|---------------|
| Housing material | Polyamide |
| Halogen free | Yes |
| Contact material | CuZn |
| Insulation components continuous temperature | 100 °C |
| Surface finish | Silver-plated |

Classification

| | |
|------------|---|
| ECLASS 8.1 | 27440603: Compact distributor for plug-in building installation |
| ETIM 6.0 | : EC002567 |
| ETIM 5.0 | EC002567: Compact distributor for plug-in building installation |
| ETIM 4.0 | EC002567: Compact distributor for plug-in building installation |