

TKE/B 25/FFD/02/2.5



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Brass nickel-plated
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66
Surface	Nickel-plated
Thread type	M
Ø Connection thread D	25
Lead	1,5
Length screw-in thread L	7 mm
Key width SW	29 mm
Total length TL	33 mm - 42 mm
Type of cable anchorage	A
Install. torques fitting	10 N/m
Install. torques cap nut	10 N/m
Impact category	6
Order no. nickel-plated	10106230
Type	TKE/B 25/FFD/02/2.5
Packing unit	1
ETIM-Classification	EC000441

Description:

IP 68 Brass cable gland for flat cable insert. EMSKV 25/ FFD for 2 x 2.5 mm twin and earth. Kit contains insert, and locknut.

13.08.2019

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk