
 <b>WANJIA</b> Relays for advanced technology	ECONOMICAL 30AMP DC COIL PC BOARD RELAY	WJ115-RELAYS
---	---	--------------



- High switching capacity - 30A for 1 Form A
- 2 contact arrangements - 1 Form A or 1 Form C
- Sealed type available
- UL/C-UL recognized

	1 Form A	1 Form C	
		N.C.	N.O.
UL/C-UL Rating			
Resistive load (cos φ=1)	30A 240VAC 30A 120VAC	10A 240VAC 10A 120VAC	20A 240VAC 20A 120VAC
Inductive load (cos φ=0.75•0.8)	15A 240VAC 15A 120VAC	10A 240VAC 10A 120VAC	10A 240VAC 10A 120VAC
Motor load	1-1/2HP 240VAC 3/4HP 120VAC	1/2HP 240VAC 3/4HP 120VAC	1-1/2HP 240VAC 3/4HP 120VAC

**SPECIFICATIONS**

**Contact**

Arrangement	1 Form A	1 Form C
Contact Material	Silver alloy	
Contact Resistance (By voltage 6V 1A)	Max.100m•	
Rating		
Max. Switching power	7200VA	N.C.: 2400VA N.O.: 4800VA
Max. Switching voltage	250VAC	
Max. Switching current	30A	N.C.: 10A N.O.: 20A
Expected life(min.ope) Mechanical(at 120 cpm)	Min.1×10 <sup>7</sup>	
Electrical(at 20 cpm)	30A 240VAC Min.1×10 <sup>5</sup>	N.O. 20A 240VAC Min.1×10 <sup>5</sup> N.C. 10A 240VAC Min.1×10 <sup>5</sup>

**Characteristics**

Operate Time	Max.15msec.	
Release Time	Max.10msec.	
Initial Insulation Resistance	Min.100M• (500 VDC)	
Initial breakdown voltage Between coil & contact Between open contacts	2500VAC (50/60Hz)for 1 min 2500VAC (50/60Hz)for 1 min.	
Shock Resistance	Functional	Min.10G
	Destruction	Min.100G
Vibration Resistance	Functional	10 to 55 Hz at double Amplitude of 1.5mm
	Destruction	10 to 55 Hz at double Amplitude of 1.5mm
Ambient temperature	-55••+85•	
Unit weight	Approx.30g	


**Coil**

Nominal operating power	Approx.0.9W
-------------------------	-------------

**TYPICAL APPLICATION**

1. Automotive
2. Air conditioner
3. Heating & ventilation
4. Home appliance

**ORDERING INFORMATION**



Type	Number of pole	Contact form	Coil voltage(DC)
WJ115	1 : 1 pole	1A : 1 Form A 1B : 1 Form B 1C : 1 Form C	5, 6, 9, 12, 18, 24, 48, 110V

**COIL DATA (at 20•)**

Nominal Voltage (VDC)	Pick-up Voltage VDC(Max.)	Drop-out Voltage VDC(Min.)	Coil Resistance (•)±10%	Nominal operating Power (W)	Max.Allowable Voltage
5	3.75	0.5	27	0.926	120% of nominal Voltage
6	4.50	0.6	40	0.900	
9	6.75	0.9	97	0.835	
12	9.00	1.2	155	0.930	
15	11.25	1.5	256	0.879	
18	13.5	1.8	380	0.853	
24	18.00	2.4	660	0.873	
48	36.0	4.8	2560	0.900	
110	82.5	11.0	13400	0.900	

**DIMENSIONS**

Unit: mm

