



## Product information

# Weller®

**WXR 3032**

Code No. : **T0053503699**

Reworkstation

3-Kanal Versorgungseinheit, 400 W

Rework station 3 channels, 230 V, 420 W with hot air iron WXHAP 200, 200 W, desoldering iron WXDV 120, 120 W and soldering iron WXP 65, 65 W with Power Response Heating Technology

### Technical Data



This station is ESD safe.

<b>Dimensions L x W x H:</b>	273 x 235 x 102 mm (10,75 x 9,25 x 4,02 inch)
<b>Weight:</b>	ca. 6,7 kg
<b>Mains supply voltage:</b>	230 V, 50 Hz / 120 V, 60 Hz / 100 V 50/60 Hz
<b>Power consumption:</b>	420 W (600 W)
<b>Safety class:</b>	I, antistatic housing III, soldering tool
<b>Fuse:</b>	Overcurrent release 230 V; 2,0 A 120 V; 4,0 A
<b>Temperature accuracy:</b>	± 9°C (± 17°F) depends on tool (WXHAP ± 30°C / ± 80°F)
<b>Temperature stability:</b>	± 2°C (± 4°F)
<b>Equipotential bonding:</b>	Via 3.5 mm pawl socket on back of unit
<b>Display:</b>	240 x 88 dots / Backlighting
<b>USB-Schnittstelle:</b>	The control unit comes with a USB port for installing firmware updates, configuration and monitoring.

<b>Built in pump:</b>	(Intermittent operation 30/30 s) Max. vacuum: 0,7 bar Max. flow: 18l/min Hot air max. 15 l/min
-----------------------	---

---

<b>Additional vacuum pump:</b>	Max. vacuum: 0,7 bar Max. flow: 18l/min
--------------------------------	--

---

Weller®