


Configuration


Enlarger	Brass CuZn39Pb3, nickel-plated
External thread	Pg as per DIN 40430
Internal thread	Pg as per DIN 40430

Properties

	<ul style="list-style-type: none"> enlarger for threaded or clearance holes to larger thread size
Temperature range	-60°C +200°C
Protection grade	dependent on the combination with other components



Features

A	B	L	H	Da	Di		Part No.
		mm	mm	mm	mm	Piece	
Pg 7	Pg 9	5	15	17	10	100	709
Pg 9	Pg 11	6	16,5	20	12	100	911
Pg 9	Pg 13,5	6	17,5	22	12	100	913
Pg 11	Pg 13,5	6	17,5	22	15	100	1113
Pg 11	Pg 16	6,5	19	24	15	100	1116
Pg 11	Pg 21	6,5	21	30	15	100	1121
Pg 13,5	Pg 16	6,5	19	24	17	100	1316
Pg 13,5	Pg 21	6,5	21	30	17	100	1321
Pg 16	Pg 21	6,5	21	30	18,5	100	1621
Pg 16	Pg 29	6,5	22,5	39	18,5	50	1629
Pg 21	Pg 29	7	23	39	24	50	2129
Pg 29	Pg 36	8	27,5	50	32	25	2936
Pg 36	Pg 42	9	31	57	42	10	3642
Pg 42	Pg 48	10	33	64	48	10	4248