



Sample photo

Order symbol: PC C 65 T
Product nbr: 8724005
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074002020
EI. number:
 Finland 3423505
 Denmark 8212001527
 Italy 7202020
 Sweden 2536838

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:			Rating:	
	L	W	H	
mm:	140	80	65	Ingress Protection (EN 60529): IP 66/67
inch:	5.5	3.1	2.6	Impact Resistance (EN 50102): IK 08
Materials:			Electrical insulation: Totally insulated	
Material:	PC		Halogen free (DIN/VDE 0472, Part 815): Yes	
Base colour:	RAL 7035		UV resistance: UL 508	
Cover colour:	Clear transparent		Flammability Rating (UL 746 C 5): UL 94 5V	
Cover screws material:	Polyamide		Glow Wire Test (IEC 695-2-1) °C: 960	
Cover screws colour:	Grey		NEMA Class: NEMA 1, 4X, 6, 6P, 12, 13	
Gasket material:	Polyurethane		Certificates:	
Temperatures:			Germanischer Lloyd (GL)	
Short term:	-40 ... 120 °C		Underwriters Laboratories	
Continuous:	-40 ... 80 °C		Canadian Standards Association	
Short term:	-40 ... 250 °F		Fimko	
Continuous:	-40 ... 175 °F		Europe EN 50298 1998	
Accessories:			UL Canada	
C-MP	Mounting plate		Gost R	
CHM-3	DIN-35 Mounting rail			
FP 22040	Mounting foot kit (2 pcs)			

