



Sample photo

Order symbol: PC D 65 T
Product nbr: 8724007
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074002105
EI. number:
 Finland 3423509
 Denmark 8212001569
 Italy 7202030
 Sweden 2536844

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions: **L** **W** **H**

mm: 170 80 65
inch: 6.7 3.1 2.6

Materials:

Material: PC
Base colour: RAL 7035
Cover colour: Clear transparent
Cover screws material: Polyamide
Cover screws colour: Grey
Gasket material: Polyurethane

Temperatures:

Short term: -40 ... 120 °C
Continuous: -40 ... 80 °C
Short term: -40 ... 250 °F
Continuous: -40 ... 175 °F

Accessories:

D-MP Mounting plate
 DH-3 DIN-35 Mounting rail
 FP 22040 Mounting foot kit (2 pcs)

Rating:

Ingress Protection (EN 60529): IP 66/67
Impact Resistance (EN 50102): IK 08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 94 V5
Glow Wire Test (IEC 695-2-1) °C: 960
NEMA Class: NEMA 1, 4X, 6, 6P, 12, 13

Certificates:

Germanischer Lloyd (GL)
Underwriters Laboratories
Canadian Standards Association
Fimko
Europe EN 50298 1998
UL Canada
Gost R

